SZSF512X

Empty enclosure, Prisma XS, floor-standing, without door, IP30, (W) 1300 mm x (H) 1980 mm x (D) 210 mm



Main Range

| Range | Prisma |
|------------------------------------|--|
| Product name | Prisma XS |
| Product or component type | Enclosure |
| Enclosure type | Empty enclosure |
| Enclosure/cubicle description | Floor-standing enclosure depth 210 mm |
| Width | 1300 mm |
| Height | 1980 mm |
| Depth | 210 mm |
| Embedding depth | 190 mm |
| Number of 18 mm modules per row | 60 x 12 |
| Electrical insulation class | Class II |
| Additional information | Can be combined side by side and one on top of another |
| Condition of use | Indoor |
| Provided equipment | 10 x cable entry plate |
| Type of front cover | Without |
| | |

Complementary

| Cable entry | Entry from the bottom or from the top |
|-------------------------------|---------------------------------------|
| Enclosure mounting | Floor-standing |
| Mounting support | Hollow wall Concrete |
| 9 mm pitches | 1440 |
| Total number of 18 mm modules | 720 |
| [In] rated current | 630 A |
| Enclosure material | Enclosure: powder coated steel |
| Net weight | 54.500 kg |
| Colour | White (RAL 9016) |
| | |

Environment

| IP degree of protection | IP30 | |
|-------------------------|-------------------------------------|--|
| IK degree of protection | IK09 | |
| Standards | EN/IEC 61439-1 VDE 0660 part 600 | |

Packing Units

| Unit Type of Package 1 | PCE | |
|------------------------------|----------|--|
| Number of Units in Package 1 | 1 | |
| Package 1 Height | 132.0 cm | |
| Package 1 Width | 23.0 cm | |
| Package 1 Length | 200.0 cm | |
| Package 1 Weight | 60.0 kg | |