

SZXPE27N

Earth terminal block, Prisma XS, 6 screw connections 2.5 to 16 mm², 21 screwless connections 1.5 to 4 mm²



Main

Range	Prisma
Product or component type	Earth terminal block

Complementary

Accessory / separate part category	Electrical accessory
[In] rated current	63 A
[Ui] rated insulation voltage	400 V
Number of terminal blocks	1 earth (screw and screwless terminals) with 27 outgoing
Distribution block outgoing	2.5...16 mm ² for earth incoming 1.5...4 mm ² for earth outgoing
Connections - terminals	Screw connection (earth) , 6 x 2.5...16 mm ² Screwless connection (earth) , 21 x 1.5...4 mm ²
Net weight	0.150 kg
Range compatibility	Prisma Prisma XS

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	18.0 cm
Package 1 Width	25.0 cm
Package 1 Length	3.5 cm
Package 1 Weight	150.0 g
Unit Type of Package 2	S02
Number of Units in Package 2	30
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	4.815 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.