Product data sheet
Characteristics

TPCCIF04
external HMI for TransferPacT Active automatic, external display, surface mounting, IP40

Green Premium™

Main

Range of product	TransferPacT
Product or component type	Display module Control block
Accessory / separate part category	Control accessory Display and signalling accessory
Function of module	Display of operating modes and alarm

Complementary

Control type	Remote control Push-button
Mounting mode	Surface mounting
Mounting support	Door cut-out Base
Display type	LCD display
Display resolution	128 x 96 pixels
Height	120.5 mm
Width	90.5 mm
Depth	56 mm
Net weight	200 g

Environment

IP degree of protection	Front cover: IP40
Ambient air temperature for operation	-25…70 °C
Ambient air temperature for storage	-40…85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.0 cm
Package 1 Width	14.0 cm
Package 1 Length	18.0 cm
Package 1 Weight	350.0 g
Unit Type of Package 2	S02
Number of Units in Package 2	4
Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	1.82 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Life Is On | Schneider Electric