



Main

Range of product	TransferPacT
Product or component type	I/O module
Device application	Signalling

Complementary

Auxiliary contact composition	1 NO
Signalling function	Fire protection (transfer to off position)
Auxiliary connection terminal	Screw clamp terminal 0.05...2.6 mm ²
Mounting mode	Plug-in
Mounting position	Left-bottom
Maximum input current	10 mA 24 V DC +/- 20 %
[Ui] rated insulation voltage	30 V DC
Tightening torque	0.6 N.m +/- 0.1 N.m
Height	56.5 mm
Width	20 mm
Depth	69 mm
Net weight	40 g
Accessory / separate part category	Signalling accessory

Environment

IP degree of protection	IP20
Pollution degree	3

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.65 cm
Package 1 Width	6.9 cm
Package 1 Length	2 cm
Package 1 Weight	140 g

Offer Sustainability

Sustainable offer status	Green Premium product
RECh Regulation	RECh Declaration
RECh free of SVHC	Yes
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes

China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
