TPSAUX32

auxiliary contact, TransferPacT, indication for source I and souce II





Main

Range of product	TransferPacT
Product or component type	Auxiliary Contact Module
Device application	Signalling

Complementary

Complementary	
Auxiliary contact composition	2 NO + 2 NC
Signalling function	Switch position (SI and SII)
Auxiliary connection terminal	Screw clamp terminal
Mounting mode	Clip-on
Mounting position	Right-angled
Tightening torque	0.6 N.m +/- 0.1 N.m
Height	90 mm
Width	17.5 mm
Depth	49.5 mm
Net weight	60 g
Accessory / separate part category	Signalling accessory

Environment

IP degree of protection	IP20	
Pollution degree	3	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.3 cm
Package 1 Width	5.8 cm
Package 1 Length	12.0 cm
Package 1 Weight	180.0 g
Unit Type of Package 2	S02
Number of Units in Package 2	18
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	3.5 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	☐ End Of Life Information