

Product data sheet

Characteristics

VB300R-15BS

VB300R Ball Valve, 3-Way, DN15, Rp 1/2, Kvs 8.7, PN40, Pop Top Connection, PTFE / Viton seals.



Main

Product or component type	Valve
Valve type	Ball
Valve product series	VB300R
Valve model	VB300R-15BS 8.7T 00
Medium compatibility	Glycol 25 % Glycol 30 % Glycol 50 % Glycol 60 % Water
Valve configuration	3-Way
Valve connection type	Rp Internal
Body size	15 mm (1/2 in)
Pipe size	DN15
Flow characteristic	Equal percentage
Flow coefficient	10.06 cv 8.7 kvs
Pressure allowable static	40 bar
Pressure class	PN40
Operating fluid temperature	-7...120 °C
Pressure fluid max delta P quiet service	137.90 kPa
Pressure fluid max delta P normal life	206.84 kPa
Seat leakage	Port A: Class IV (0.01 %)
Trim material	Stainless steel
Material ball	Stainless steel
Material characterizing insert	Glass-filled PEEK
Seat material	Port A: PTFE (polytetrafluoroethylene) Port B: PTFE (polytetrafluoroethylene)
Stem material	Stainless steel
Targeted region	Europe Asia Pacific. Australia.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Offer Sustainability

EU RoHS Directive	Not applicable, out of EU RoHS legal scope
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.