



### Main

|                                       |  |
|---------------------------------------|--|
| Product or component type             | Pre-assembled cable kit for safe torque off signal - 20 M            |
| Accessory / separate part type        | Cable  |
| Accessory / separate part category    | Connection accessories   |
| Accessory / separate part destination | For drives with printed circuit board connectors for safe torque off |
| Cable length                          | 20 m   |
| Additional information                | With integrated cable entry with strain relief                       |

### Complementary

|                       |   |
|-----------------------|---|
| Range compatibility   | Lexium ILE<br>Lexium ILA<br>Lexium ILS  |
| Electrical connection | 1 connector M8 for safe torque off<br>Cable end open for drive<br>Printed circuit board connector |
| Net weight            | 3 kg  |

### Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Number of Units in Package 1 | 1       |
| Package 1 Height             | 10.0 cm |
| Package 1 Width              | 30.0 cm |
| Package 1 Length             | 30.0 cm |
| Package 1 Weight             | 3.0 kg  |

### Offer Sustainability

|                            |  |
|----------------------------|--|
| REACH Regulation           | <a href="#">REACH Declaration</a>  |
| REACH free of SVHC         | Yes  |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a> |
| Toxic heavy metal free     | Yes  |
| Mercury free               | Yes  |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>   |
| RoHS exemption information | <a href="#">Yes</a>  |
| PVC free                   | Yes  |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|