# VW3L40210

# insert - 2 female M8 for 2 I/O signals + 1 male M8 for safe torque off safety



Main	
Range of product	Lexium integrated drive
Product or component type	Insert for communication interface
Accessory / separate part type	Connection accessories
Accessory / separate part category	Connection accessories
Accessory / separate part destination	For drives

## Complementary

Electrical connection	1 male connector M8 4 pins for for connection of signals for safe torque off 2 female connectors M8 3 pins for for connection of 2 I/O signals
Kit composition	1 insert with connectors 1 sealing insert
Input/output type	2 I/O signals + 1 STO signal
Net weight	0.036 kg

### **Packing Units**

r doming of the		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	4.0 cm	
Package 1 Width	5.2 cm	
Package 1 Length	9.0 cm	
Package 1 Weight	36.0 g	
Unit Type of Package 2	S01	
Number of Units in Package 2	30	
Package 2 Height	15.0 cm	
Package 2 Width	15.0 cm	
Package 2 Length	40.0 cm	
Package 2 Weight	1.242 kg	

### Offer Sustainability

REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EV RoHS  Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes
PVC free	Yes

Warranty 18 months