VW3M5501R100

power cordset 4x1,5mm² + 2x1mm² + 2x0,14mm² 10 m one end w M23 industrial con.





Main

Range of product	Altivar
Accessory / separate part type	Power cable
Accessory / separate part category	Connection accessories
Accessory / separate part destination	Between synchronous motor and variable speed drive
Range compatibility	Altivar Machine ATV320 Altivar 32
Cable length	10 m
Type of cable	Shielded cable

Complementary

- Compromontary		
Product compatibility	Synchronous motor BMP (flange size: 140 mm, 1 stack(s) type C	
	Synchronous motor BMP (flange size: 140 mm, 1 stack(s) type F	
	Synchronous motor BMP (flange size: 140 mm, 2 stack(s) type C	
	Synchronous motor BMP (flange size: 70 mm, 1 stack(s) type R	
	Synchronous motor BMP (flange size: 70 mm, 1 stack(s) type F	
	Synchronous motor BMP (flange size: 70 mm, 2 stack(s) type R	
	Synchronous motor BMP (flange size: 70 mm, 2 stack(s) type F	
	Synchronous motor BMP (flange size: 100 mm, 1 stack(s) type R	
	Synchronous motor BMP (flange size: 100 mm, 1 stack(s) type F	
	Synchronous motor BMP (flange size: 100 mm, 2 stack(s) type R	
	Synchronous motor BMP (flange size: 100 mm, 2 stack(s) type F	
Electrical connection	1 connector M23 8 pin(s) synchronous motor side	
	1 free endvariable speed drive side	
Cable composition	4 x 1.5 mm² + 2 x 1 mm² + 2 x 0.14 mm²	
Net weight	2.44 kg	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.500 cm
Package 1 Width	41.700 cm
Package 1 Length	37.800 cm
Package 1 Weight	2.730 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes

Environmental Disclosure	☑ Product Environmental Profile	
Circularity Profile	End Of Life Information	
PVC free	Yes	
Contractual warranty		
Warranty	18 months	