

Product data sheet

Characteristics

VW3M8222R250

cable for creating control cord sets, 3 x (2 x 0.14 mm²) + (2 x 0.34 mm²), 25m



Main

| | |
|---------------------------------------|---|
| Range of product | Lexium |
| Accessory / separate part category | Connection accessory |
| Accessory / separate part type | Encoder cable |
| Product or component type | Cable |
| Device application | For creating control cordsets for SinCos Hiperface encoders |
| Accessory / separate part destination | From servo motor to servo drive |
| Cable composition | 3 x (2 x 0.14 mm ²) + (2 x 0.34 mm ²) |

Complementary

| | |
|---------------------|--|
| Range compatibility | Lexium 32 Altivar Machine ATV340 Altivar Process ATV900 |
| Cable length | 25 m |
| Net weight | 1.4 kg |

Packing Units

| | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 5.0 cm |
| Package 1 Width | 30.0 cm |
| Package 1 Length | 30.0 cm |
| Package 1 Weight | 1.625 kg |
| Unit Type of Package 2 | S04 |
| Number of Units in Package 2 | 6 |
| Package 2 Height | 30.0 cm |
| Package 2 Width | 40.0 cm |
| Package 2 Length | 60.0 cm |
| Package 2 Weight | 11.002 kg |

Offer Sustainability

| | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| | |
|---------------------|---|
| Circularity Profile | End Of Life Information |
| PVC free | Yes |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|
