

Product data sheet

Characteristics

VW3M8D2AR30

encoder cable 3m shielded, MIL connector for BCH2.H/.M/.R, CN2 plug



Main

Range of product	Lexium
Accessory / separate part category	Connection accessory
Accessory / separate part type	Encoder cable
Product or component type	Encoder cable
Device application	For BCH2 with SinCos single turn encoder
Accessory / separate part destination	From servo motor to servo drive
Cable composition	5 x (2 x 0.13 mm ²)

Complementary

Electrical connection	1 connector Firewire 6 pin(s) 1 connector MIL 17 pin(s)
Range compatibility	Lexium 28
Cable length	3 m
Net weight	1.3 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4 cm
Package 1 Width	22 cm
Package 1 Length	23 cm
Package 1 Weight	241 g
Unit Type of Package 2	S02
Number of Units in Package 2	10
Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	2.71 kg

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
PVC free	Yes

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.