

Product data sheet

Characteristics

VW3S8208R15

connecting cable, Lexium SD3, for pulse or direction signal, 5V, 1.5m, for TLM2



Main

Accessory / separate part designation	Cable for pulse/direction signal
Accessory / separate part type	Connecting cable
Accessory / separate part category	Connection accessories
Accessory / separate part destination	Between stepper drive SD326 and motion controller TLM2
Range compatibility	Lexium SD3
Cable length	1.5 m

Complementary

Product compatibility	SD326
[Uc] control circuit voltage	5 V
Electrical connection	1 connector 24-pole Molex (SD326) 1 connector SUB-D 15 (TLM2)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3 cm
Package 1 Width	40 cm
Package 1 Length	30 cm
Package 1 Weight	176 g

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.