

VZ408C-15BP04

Zone Valve, 15mm, 3-Way Bypass,
Compression, Brass, 1kvs



Main

| | |
|--|--|
| Product or component type | Valve |
| Valve type | Zone |
| Device application | Fan coil unit Chilled ceiling Terminal unit |
| Medium compatibility | Glycol 25 % Glycol 30 % Water Glycol 50 % |
| Valve configuration | 3-Way with Bypass |
| Valve connection type | Compression |
| Body size | 15 mm (1/2 in) |
| Pipe size | 15 mm |
| Flow characteristic | Uncharacterized |
| Flow coefficient B to AB | 0.92 cv 0.8 kvs |
| Flow coefficient | 1 kvs 1.16 cv |
| Pressure class | PN16 |
| Pressure fluid max delta P quiet service | 62.05 kPa |
| Pressure fluid max delta P normal life | 255.11 kPa |
| Seat leakage | Port A: Class IV-S1 (0.005 %) |
| Stem movement | Linear |
| Trim material | Brass |
| Body material | Brass |
| Stem material | Stainless steel AISI 303 |
| Seating seal material | Port A:EPDM (ethylene propylene diene monomer) |
| Stem seal material | EPDM (ethylene propylene diene monomer) |
| Targeted region | Europe Asia Pacific. Australia. |

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 5.5 cm |
| Package 1 Width | 10.0 cm |
| Package 1 Length | 13.0 cm |
| Package 1 Weight | 340.0 g |

Offer Sustainability

| | |
|----------------------------|--|
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |