

Main

Range of product	Canalis
Product name	KS
Product or component type	Elbow
Busbar description	Standard
Bar material	Aluminium
Device application	Change direction
[Ie] rated operational current	400 A at 35 °C
Direction change type	Direction 1: edgewise to right - Direction 2: edgewise to left -
Colour	White (RAL 9001)

Complementary

[Ue] rated operational voltage	230...690 V
Network frequency	50/60 Hz
Operating angle	90 °
Busbar trunking polarity	3L + N + PE
Mounting location	On trunking
Mounting position	Any position
Electrical connection	Lubricated sliding contact
Mounting mode	By screws
Width	54 mm
Height	146 mm
Length	165 Mm for side A 165 mm for side B
Net weight	3.9 kg



Environment

IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262
Standards	IEC 60439-2 IEC 61439-6


Packing Units

Package 1 Weight	3.900 kg
Package 1 Height	1.660 dm
Package 1 width	1.950 dm
Package 1 Length	2.550 dm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes

Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins



Dimensions		KSA400DLC401
------------	--	--------------

A (mm)	165
B (mm)	165
C (mm)	-
D (mm)	-
Fire barrier	No
Fire barrier position	-