

### Main

Range of product	Canalis
Product name	KS
Product or component type	Support foot
Product compatibility	KS
Fixing device mounting	Tied at riser 1st joint. unit
Maximum load	1760 kg

### Complementary

Accessory / separate part category	Fixing accessory
[Ie] rated operational current	1000.0 A
Mounting position	Vertical
Width	275 mm
Depth	225.5 mm
Height	200 mm
Net weight	7.3 kg



### Environment

Standards	IEC 61439-6 IEC 60439-2
-----------	----------------------------

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	8.759 kg
Package 1 Height	19.5 cm
Package 1 width	34 cm
Package 1 Length	43 cm
Unit Type of Package 2	P06
Number of Units in Package 2	6
Package 2 Weight	67 kg
Package 2 Height	72 cm
Package 2 width	80 cm
Package 2 Length	60 cm

### Offer Sustainability

Sustainable offer status	Green Premium product
RECh Regulation	 <a href="#">RECh Declaration</a>
RECh free of SVHC	Yes
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes

RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product

### Contractual warranty

Warranty	18 months
----------	-----------

