



Main

Range of product	Canalis
Product name	KS
Product or component type	Busbar trunking
Busbar description	Distribution length
BAR MATERIAL	Copper
Device application	Medium power distribution
[Ie] rated operational current	160 A at 35 °C
Number of tap-off outlets	6

Complementary

[Ue] rated operational voltage	230...690 V
Network frequency	50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
[Ui] rated insulation voltage	690 V
[Icw] rated short-time withstand current	4.45 kA
[Ipk] rated peak withstand current	22 kA
Electrical connection	Lubricated sliding contact
Radiated magnetic field	0.41 µT
Thermal stress limit	20.2 kA ² .s
THDI	0...15 % 160 A 15...33 % 125 A 33...100 % 100 A
Maximum voltage drop	<0.0667 V with power factor = 1 at 50 Hz with 1A for 100 m long <0.0666 V with power factor = 0.9 at 50 Hz with 1A for 100 m long <0.0665 V with power factor = 0.8 at 50 Hz with 1A for 100 m long <0.0665 V with power factor = 0.7 at 50 Hz with 1A for 100 m long
Mounting mode	By screws
Mounting position	Horizontal
Neutral position	Up
Busbar trunking polarity	3L + N + PE 3L + PEN
Dimension type	Fix
Width	146 mm
Depth	54 mm
Length	3 m
Net weight	14.6 kg

Environment

Standards	IEC 60439-2 IEC 61439-6
-----------	----------------------------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	14.6 kg
Package 1 Height	6.4 cm
Package 1 width	15 cm
Package 1 Length	309 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product