



Main

Range of product	Canalis
Product name	KS
Product or component type	Busbar trunking
Busbar description	Riser foot
BAR MATERIAL	Aluminium
Device application	Rise medium power distribution
[Ie] rated operational current	100 A at 35 °C
Number of tap-off outlets	1

Complementary

[Ue] rated operational voltage	230...690 V
Network frequency	50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
[Ui] rated insulation voltage	690 V
[Icw] rated short-time withstand current	2.6 kA
[Ipk] rated peak withstand current	15.7 kA
Electrical connection	Lubricated sliding contact
Radiated magnetic field	0.22 µT
Thermal stress limit	6.8 kA ² .s
THDI	0...15 % 100 A 15...33 % 80 A 33...100 % 63 A
Maximum voltage drop	<0.138 V with power factor = 1 at 50 Hz with 1A for 100 m long <0.13 V with power factor = 0.9 at 50 Hz with 1A for 100 m long <0.118 V with power factor = 0.8 at 50 Hz with 1A for 100 m long <0.106 V with power factor = 0.7 at 50 Hz with 1A for 100 m long
Mounting mode	By screws
Mounting support	Foot riser
Mounting position	Vertical - neutral on right
Neutral position	Right
Busbar trunking polarity	3L + N + PE
Dimension type	Fix
Width	146 mm
Depth	54 mm
Height	800 mm
Length	0.8 m
Net weight	5.4 kg

Environment

Standards	IEC 61439-6 IEC 60439-2
-----------	----------------------------

Packing Units

Package 1 Weight	6.500 kg
Package 1 Height	0.630 dm
Package 1 width	1.660 dm
Package 1 Length	8.885 dm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------

