XZCR1111064D03

Telemecanique Safety light curtains XUSL, Series connection jumper, 2 straight M12, Female/Female con., 0.3 m, 5 pins



Main

TTT CALL	
Range of product	Telemecanique Safety light curtains XUSL
Accessory / separate part type	Jumper cable
Accessory / separate part category	Connection accessory
Accessory / separate part destination	Safety light curtain master/slave XCSR RFID safety switch

Complementary

Product compatibility	XUSL2	
, , , , , , , , , , , , , , , , , , ,	XCSRC.2M12	
	XUSL4	
Connector type	M12 female 5 pins straight	
Wire insulation material	PUR	
Collar material	Nickel plated brass	
Cable outer diameter	5 mm	
Cable composition	5 x 0.34 mm²	
Cable length	0.3 m	

Environment

IP degree of protection	IP67 IP65	
	IP69K	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	40 g	
Package 1 Height	2.5 cm	
Package 1 width	8 cm	
Package 1 Length	17 cm	

Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	€Yes