# XZCR1111064D10

Telemecanique Safety light curtains XUSL, Series connection jumper, 2 straight M12, Female/Female con., 10 m, 5 pins



#### Main

| Telemecanique Safety light curtains XUSL                     |
|--|
| Jumper cable   |
| Connection accessory   |
| Safety light curtain master/slave<br>XCSR RFID safety switch |
|  |

## Complementary

| Product compatibility    | XUSL2                      |  |
|--------------------------|----------------------------|--|
|                          | XCSRC.2M12                 |  |
|                          | XUSL4                      |  |
| Connector type           | M12 female 5 pins straight |  |
| Wire insulation material | PUR                        |  |
| Collar material          | Nickel plated brass        |  |
| Cable outer diameter     | 5 mm                       |  |
| Cable composition        | 5 x 0.34 mm²               |  |
| Cable length             | 10 m                       |  |

### **Environment**

| IP degree of protection | IP69K<br>IP65 |
|-------------------------|---------------|
|                         | IP67          |

#### **Packing Units**

| Unit Type of Package 1       | PCE   |  |
|------------------------------|-------|--|
| Number of Units in Package 1 | 1     |  |
| Package 1 Weight             | 378 g |  |
| Package 1 Height             | 4 cm  |  |
| Package 1 width              | 20 cm |  |
| Package 1 Length             | 20 cm |  |
|                              |       |  |

#### Offer Sustainability

| REACh Regulation           | REACh Declaration  |
|----------------------------|--|
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free               | Yes  |
| RoHS exemption information | €Yes   |