

Product data sheet

Characteristics

XZCRA151140A2

Jumper cable XZ, male straight M12 3 pin, female straight M12 3 pin, PVC 2 m



Main

Accessory / separate part category	Cabling accessory
Accessory / separate part type	Jumper cable

Complementary

Jumper cable end 1	M12 male 3 pins straight connector with screw-on and clip-on
Jumper cable end 2	M12 female 3 pins straight connector with screw-on and clip-on
Collar material	Metal
Cable composition	3 x 0.34 mm ²
Cable length	2 m
Cable outer diameter	5 mm
[Ue] rated operational voltage	250 V AC 300 V DC
[In] rated current	4 A
Insulation resistance	>= 1000 MOhm
Maximum resistance across terminals	5000 mOhm
Net weight	0.095 kg

Environment

IP degree of protection	IP69K
Ambient air temperature for operation	-25...85 °C static

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	100 g
Package 1 Height	2 cm
Package 1 width	16 cm
Package 1 Length	16 cm

Offer Sustainability


REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes

Contractual warranty

Warranty

18 months

Dimensions



L : Length of cable

Connections and Schemes

