XZCRA151141C5

jumper cable XZ - male straight M12 4-pin female straight M12 4-pin - PVC 5m



Main Accessory / separate Cabling accessory part category Accessory / separate Jumper cable part type

Complementary

Complementary		
Jumper cable end 1	M12 male 4 pins straight connector with screw-on and clip-on	
Jumper cable end 2	M12 female 4 pins straight connector with screw-on and clip-on	
Collar material	Metal	
Cable composition	4 x 0.34 mm ²	
Cable length	5 m	
Cable outer diameter	5.3 mm	
[Ue] rated operational voltage	250 V AC 300 V DC	
[In] rated current	4 A	
Insulation resistance	>= 1000 MOhm	
Maximum resistance across terminals	5000 mOhm	
Net weight	0.22 kg	

Environment

IP degree of protection	IP69K
Ambient air temperature for operation	-2585 °C static

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	236 g	
Package 1 Height	2 cm	
Package 1 width	17 cm	
Package 1 Length	19 cm	

Offer Sustainability


REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes

Warranty 18 months

Product data sheet Dimensions Drawings

XZCRA151141C5

Dimensions



L: Lenght of cable

Product data sheet Connections and Schema

XZCRA151141C5

Connections and Schemes

