# **INDICATING BEACON 250V 10W +OPTIONS**





#### Main

Range of product	Harmony XVB Universal
Product or component type	Complete beacon
Beacon or indicator bank unit type	Base unit direct or tube fixing Illuminated unit
Signalling type	Steady
Mounting diameter	70 mm
Component name	XVBL
Material	Glass reinforced polyamide: base unit Polycarbonate: illuminated unit
Light source	Bulb not included, yellow
Bulb type	Incandescent with BA 15d base Protected LED
[Us] rated supply voltage	<= 250 V
Maximum power dissipation in W	7 W

#### Complementary

Connections - terminals	Screw clamp terminals, <= 1 x 1.5 mm² with cable end	
[Ui] rated insulation voltage	250 V conforming to IEC 60947-1	
Nominal voltage limit	0.851.1 Un conforming to IEC 60947-5-1	
[Uimp] rated impulse withstand voltage	IEC 60947-1 4 kV	
CAD overall width	70 mm	
CAD overall height	139 mm	
CAD overall depth	70 mm	
Terminals description ISO n°1	(GND)GROUND (COM-1)PW	
Net weight	0.26 kg	

#### Environment

Pollution degree	2	
Product certifications	UL 508 CCC GOST CSA C22-2 No 14	
Standards	EN/IEC 60947-5-1	
Protective treatment	TC	
Ambient air temperature for operation	-2550 °C: LED -2570 °C: incandescent	
Ambient air temperature for storage	-4070 °C	
Electrical shock protection class	Class I on support tube conforming to IEC 61140 Class II on base unit conforming to IEC 61140	
IP degree of protection	IP65 on fixing base XVBZ0. conforming to IEC 60529 IP66 on base unit conforming to IEC 60529	
NEMA degree of protection	NEMA 4X conforming to UL 508 (indoor)	

# Packing Units

3	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	261 g
Package 1 Height	8 cm
Package 1 width	8 cm
Package 1 Length	14.5 cm
Unit Type of Package 2	S03
Number of Units in Package 2	18
Package 2 Weight	5.171 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm


# Offer Sustainability

Green Premium product
☑ REACh Declaration
Pro-active compliance (Product out of EU RoHS legal scope) EVEU RoHS
Yes
₫Yes
☐ China RoHS Declaration
Product Environmental Profile
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

## Illuminated Beacon for BA 15d Bulb or LED

## Dimensions



# Product data sheet Connections and Schema

# XVBL38

## Illuminated Beacon

## Wiring Diagram

