XVR12B04

120mm Rotating Mirror Red 24VAC-DC





Main

Range of product	Harmony XVR
Product or component type	Prewired rotating mirror beacon
Sound signalling	Without
Device short name	XVR
Mounting diameter	120 mm
IP degree of protection	IP23 conforming to IEC 60529
[Us] rated supply voltage	24 V AC/DC
Light source	High luminosity LED, red

Complementary

Material	ABS (acrylonitrile butadiene-styrene): body part AS: globe	
CAD overall width	120 mm	
CAD overall depth	120 mm	
Net weight	0.5 kg	
Marking	CE	
Product mounting	By 3 M5 screws	
Supply voltage limits	1930 V DC 21.626.4 V AC	
[Uimp] rated impulse withstand voltage	0.8 kV	
Current consumption	125 mA	
Flashing frequency	2.3 Hz	
Clamping connection capacity	0.83 mm²	
AWG gauge	AWG 18	
Cable length	400 mm	

Environment

Ziivii oiiiiioiit		
Standards	EN 61000-6-2 EN 61000-6-4	
Protective treatment	TC	
Ambient air temperature for storage	-3570 °C	
Ambient air temperature for operation	-1050 °C	
Electrical shock protection class	Class II conforming to IEC 61140	

Packing Units

Package 1 Weight	0.612 kg	
Package 1 Height	1.950 dm	
Package 1 width	1.380 dm	
Package 1 Length	1.400 dm	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☐ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	☐ End Of Life Information


Contractual warranty


Warranty	18 months

XVR12B04

Rotating Mirror Beacon

Dimensions





Product data sheet Mounting and Clearance

XVR12B04

Rotating Mirror Beacon

Panel Cut-out

