## ZBVB37

Light block, Harmony XB4, Harmony XB5, green for head Ø22 mm integral LED 24 V pins





## Main

Range of product	Harmony XB4 Harmony XB5
Product or component type	Light block
Device short name	ZBV
Sale per indivisible quantity	5
Connections - terminals	Pins for printed circuit board
Signalling type	Steady
Light source	Protected LED
Bulb base	Integral LED
Light block supply	Direct
Light source colour	Green
[Us] rated supply voltage	24 V AC/DC at 50/60 Hz

## Complementary

Complementary		
Net weight	0.004 kg	
Supply voltage limits	19.230 V DC 21.626.4 V AC	
Current consumption	18 mA	
Service life	100000 h at rated voltage and 25 °C	
Surge withstand	1 kV conforming to IEC 61000-4-5	
Mounting of block	Front mounting	
Electrical composition code	M1 M2 M3 M4 M5 M6 M10 MF1 P1 P2 PF1	

## Environment

Protective treatment	TH
Ambient air temperature for storage	-4070 °C
Ambient air temperature for operation	-4070 °C
IP degree of protection	IP20 conforming to IEC 60529
Standards	EN/IEC 60947-5-4 EN/IEC 60947-1 EN/IEC 60947-5-1 CSA C22.2 No 14 JIS C8201-5-1 UL 508 EN/IEC 60947-5-5 JIS C8201-1
Resistance to fast transients	2 kV conforming to IEC 61000-4-4
Resistance to electromagnetic fields	10 V/m conforming to IEC 61000-4-3
Resistance to electrostatic discharge	6 KV on contact (on metal parts) conforming to IEC 61000-4-2 8 kV in free air (in insulating parts) conforming to IEC 61000-4-2

Electromagnetic emission	Class B conforming to IEC 55011
[Us] rated supply voltage	24 V
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	3 g
Package 1 Height	2.2 cm
Package 1 width	3.3 cm
Package 1 Length	6.6 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Weight	17 g
Package 2 Height	2.2 cm
Package 2 width	3.3 cm
Package 2 Length	6.6 cm
Unit Type of Package 3	S01
Number of Units in Package 3	200
Package 3 Weight	942 g
Package 3 Height	15 cm
Package 3 width	15 cm
Package 3 Length	40 cm
Offer Sustainability	
Sustainable offer status	Green Premium product
REACh Regulation	•
	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
RoHS exemption information	€Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	☑ End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contraction Warranty		
Warranty	18 months	