



Main

Product or component type	Bellow
Accessory / separate part category	Protection accessory
Accessory / separate part destination	Emergency stop push-button For standard head
Environmental characteristic	High pressure cleaner Dustproof Humidity resistant
Sale per indivisible quantity	2

Complementary

Range compatibility	Harmony XB4 Harmony XB5
Material	EPDM
Colour	Black
Net weight	0.009 kg

Environment

IP degree of protection	IP69K
-------------------------	-------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	9 g
Package 1 Height	3.3 cm
Package 1 width	3.4 cm
Package 1 Length	3.4 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	2
Package 2 Weight	18 g
Package 2 Height	3.5 cm
Package 2 width	5 cm
Package 2 Length	8 cm
Unit Type of Package 3	S02
Number of Units in Package 3	100
Package 3 Weight	1.272 kg
Package 3 Height	15 cm
Package 3 width	30 cm
Package 3 Length	40 cm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------