Product data sheet Characteristics

990NAD21110

Modbus Plus drop cable - between Momentum I/O sub-base and T- junction - 2.4 m



Main		
Accessory / separate part category	Connection accessories	
Accessory / separate part type	Drop connection cable	
Accessory / separate part designation	Modbus Plus drop cable	
Accessory / separate part destination	Modbus Plus network	

Complementary	C	0	m	ıρ	lei	m	er	1	a	ry	
---------------	---	---	---	----	-----	---	----	---	---	----	--

o o mpromontary		
Product compatibility	STBNMP2212	
	990NAD23010	
	990NAD23020	
	990NAD23000	
	990NAD23021	
	140CPU43412U	
	140CPU31110	
	490NRP25300	
	NWBP85002	
Range compatibility	Modicon Momentum automation platform	
	Modicon Quantum automation platform	
	Advantys STB distributed I/O solutions	
	Modicon Premium automation platform	
	Lexium 15	
Cable length	2.4 m	
Electrical connection	1 male connector SUB-D 9 elbowed communication module side	
	Free end local site tap side	
Net weight	0.169 kg	

Packing Units

r doking office		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	160 g	
Package 1 Height	2.3 cm	
Package 1 width	22 cm	
Package 1 Length	22.5 cm	
Unit Type of Package 2	S03	
Number of Units in Package 2	48	
Package 2 Weight	8.5 kg	
Package 2 Height	30 cm	
Package 2 width	30 cm	
Package 2 Length	40 cm	

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	☑ China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	

Contractual warranty

Warranty	18 months	