

ZCKD239

limit switch head ZCKD - steel roller lever
plunger with protective boot



Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKD
Head type	Plunger head
Product compatibility	XCKL XCKM
Associated body	ZCKM7 ZCKM1H29 ZCKLD37H7 ZCKL1 ZCKLD37 ZCKMD35H29 ZCKM8H7 ZCKM8 ZCKLD31 ZCKLD35H7 ZCKMD31 ZCKM9H29 ZCKL5 ZCKL6H7 ZCKL5H7 ZCKMD35 ZCKM6H7 ZCKLD39 ZCKMD31H7 ZCKM7H7 ZCKMD37H29 ZCKM5H7 ZCKMD39 ZCKM6H29 ZCKMD39H29 ZCKMD31H29 ZCKMD37 ZCKL7H7 ZCKM6 ZCKMD39H7 ZCKM5 ZCKL8H7 ZCKMD37H7 ZCKM7H29 ZCKLD39H7 ZCKLD31H7 ZCKM5H29 ZCKL6 ZCKL1H7 ZCKL7 ZCKLD35 ZCKL8 ZCKM8H29 ZCKM9 ZCKM1H7 ZCKM1 ZCKMD35H7
Movement of operating head	Rotary Linear
Type of operator	Roller lever plunger spring return metal (with protective boot)
Type of approach	Lateral approach, 1 direction

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Complementary

Switch actuation	By 30° cam
Positive opening	With
Head material	Plastic

Environment

Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...70 °C
Environmental characteristic	Standard environment

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	94 g
Package 1 Height	3.4 cm
Package 1 width	8.8 cm
Package 1 Length	7.2 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------