
ZCKD34

Limit switch head, Limit switches XC Standard, ZCKD, steel ball bearing mounted roller lever





Main

IVICIII	
Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKD
Head type	Rotary head
Product compatibility	XCKS
Associated body	ZCKS7 ZCKSD39H29 ZCKSD37H29 ZCKSD35H29 ZCKS6H29 ZCKS9H29 ZCKS1 ZCKS2 ZCKS6 ZCKS2H29 ZCKSB37 ZCKSBH29 ZCKSD37 ZCKSBH29 ZCKSD35 ZCKSLH29 ZCKSD35 ZCKS1 ZCKS5 ZCKS1H29 ZCKSD39 ZCKSD39 ZCKSD39 ZCKSD31 ZCKSD31 ZCKSPH29
Movement of operating head	Rotary
Type of operator	Roller lever spring return metal (ball bearing mounted)
	Lateral approach, 2 directions

Complementary

Switch actuation	By 30° cam
Positive opening	With
Head material	Plastic

Environment

Ambient air temperature for operation	-2570 °C
Ambient air temperature for storage	-4070 °C
Environmental characteristic	Standard environment

Packing Units

t Type of Package 1	PCE	
mber of Units in Package 1	1	
ckage 1 Weight	93 g	
ckage 1 Height	3.4 cm	
ckage 1 width	6.3 cm	
ckage 1 Length	7.6 cm	
kage 1 Length	7.6 cm	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months	