

ZCKD54

Limit switch head, Limit switches XC Standard, ZCKD, steel square rod lever 3 mm L = 125 mm



Main

| | |
|----------------------------|---|
| Range of product | Telemecanique Limit switches XC Standard |
| Series name | Standard format |
| Product or component type | Limit switch head |
| Device short name | ZCKD |
| Head type | Rotary head |
| Product compatibility | XCKS |
| Associated body | ZCKSD39H29 ZCKS2 ZCKS7 ZCKSD31H29 ZCKSD39 ZCKS9H29 ZCKS9 ZCKS8H29 ZCKS7H29 ZCKS6 ZCKSD31 ZCKS5 ZCKSD37 ZCKS5H29 ZCKSD37H29 ZCKS1H29 ZCKS1 ZCKSD35 ZCKS6H29 ZCKS2H29 ZCKSD35H29 ZCKS8 |
| Movement of operating head | Rotary |
| Type of operator | Rod lever spring return metal (square rod 3 mm, L = 125 mm) |
| Type of approach | Lateral approach, 2 directions |

Complementary

| | |
|------------------|--------------------|
| Switch actuation | By any moving part |
| Positive opening | Without |
| Head material | Plastic |

Environment

| | |
|---------------------------------------|----------------------|
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -40...70 °C |
| Environmental characteristic | Standard environment |

Packing Units

| | |
|------------------------------|--------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 100 g |
| Package 1 Height | 3.3 cm |
| Package 1 width | 6.5 cm |
| Package 1 Length | 22 cm |

| | |
|------------------------------|-------|
| Unit Type of Package 2 | S01 |
| Number of Units in Package 2 | 8 |
| Package 2 Weight | 994 g |
| Package 2 Height | 15 cm |
| Package 2 width | 15 cm |
| Package 2 Length | 40 cm |

Offer Sustainability

| | |
|--------------------------|---|
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Not applicable, out of EU RoHS legal scope |
| Environmental Disclosure | Product Environmental Profile |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|