



### Main

|                            |  |
|----------------------------|--|
| Range of product           | Telemecanique Limit switches XC Standard   |
| Series name                | Standard format  |
| Product or component type  | Limit switch head  |
| Device short name          | ZCKE   |
| Head type                  | Multi-directional head   |
| Product compatibility      | XCKJ   |
| Associated body            | ZCKJ2H7<br>ZCKJ1<br>ZCKJD31H7<br>ZCKJ8H29<br>ZCKJD35<br>ZCKJ21H29<br>ZCKJD39H29<br>ZCKJ7H29<br>ZCKJD37H7<br>ZCKJD37H29<br>ZCKJ11H29<br>ZCKJ9<br>ZCKJ1H7<br>ZCKJ6<br>ZCKJ1H29<br>ZCKJ5<br>ZCKJ8<br>ZCKJ7<br>ZCKJ2<br>ZCKJ21H7<br>ZCKJD37<br>ZCKJD35H29<br>ZCKJ9H29<br>ZCKJ5H7<br>ZCKJ21<br>ZCKJ6H7<br>ZCKJ7H7<br>ZCKJ2H29<br>ZCKJD31<br>ZCKJD35H7<br>ZCKJ8H7<br>ZCKJD39<br>ZCKJ11H7<br>ZCKJ11<br>ZCKJD31H29<br>ZCKJ9H7<br>ZCKJD39H7<br>ZCKJ5H29<br>ZCKJ6H29 |
| Movement of operating head | Multi-directional  |
| Type of operator           | Cat's whisker spring return  |
| Type of approach           | Multi-directional approach   |

### Complementary

|                  |                    |
|------------------|--------------------|
| Switch actuation | By any moving part |
| Positive opening | Without            |
| Net weight       | 0.115 kg           |
| Head material    | Metal              |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

|                                       |                 |
|---------------------------------------|-----------------|
| Ambient air temperature for operation | -40...70 °C     |
| Ambient air temperature for storage   | -40...70 °C     |
| Environmental characteristic          | Low temperature |

## Packing Units

|                  |          |
|------------------|----------|
| Package 1 Weight | 0.115 kg |
| Package 1 Height | 1.600 dm |
| Package 1 width  | 0.360 dm |
| Package 1 Length | 0.360 dm |

## Offer Sustainability

|                            |  |
|----------------------------|--|
| Sustainable offer status   | Green Premium product  |
| REACH Regulation           | <a href="#">REACH Declaration</a>  |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes  |
| RoHS exemption information | <a href="#">Yes</a>  |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>  |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|