



The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.



Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCE
Head type	Plunger head
Product compatibility	XCKD XCKP XCMD XCKT

Associated body	ZCP35 ZCP29 ZCT27N12 ZCMD37L2 ZCD37 ZCMD81L5 ZCMD25L1 ZCP26 ZCMD39L1 ZCD31 ZCD28 ZCP39 ZCMD61M12 ZCMD81L2 ZCT26P16 ZCD21M12 ZCP21 ZCD26 ZCMD21L08U78 ZCP25 ZCT25P16 ZCP31 ZCMD37L5 ZCT28G11 ZCT21G11 ZCMD39L5 ZCT25G11 ZCD39 ZCMD41L1 ZCT21P16 ZCP28 ZCMD41L5 ZCMD81L1 ZCMD69C12 ZCMD39L2 ZCD25 ZCP27 ZCD29M12 ZCT28N12 ZCT26N12 ZCMD25L5 ZCMD21M12 ZCMD21C12 ZCD21 ZCMD21L08R12 ZCMD41L2 ZCP29M12 ZCT21N12 ZCP37 ZCMD61C12 ZCMD25L2 ZCT28P16 ZCT26G11 ZCMD21L1 ZCMD29L1 ZCMD21L5 ZCMD37L1 ZCD29 ZCMD29C12 ZCMD29L2 ZCMD21L2 ZCT27P16 ZCD27 ZCD35 ZCMD29L5 ZCP21M12 ZCT25N12 ZCT27G11
Movement of operating head	Linear
Type of operator	End plunger spring return metal (adjustable)
Type of approach	Vertical approach, 1 direction

Complementary

Positive opening	With
------------------	------

Environment

Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...70 °C
Environmental characteristic	Standard environment

Packing Units

Package 1 Weight	0.023 kg
Package 1 Height	0.200 dm
Package 1 width	0.600 dm
Package 1 Length	0.650 dm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------