

# ZCE2A

Limit switch head, Limit switches XC Standard,  
ZCE, steel roller plunger with silicone boot



The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.



### Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCE
Head type	Plunger head
Product compatibility	XCKD XCMD XCKT XCKP

Associated body	ZCMD81L2 ZCMD21C12 ZCMD37L2 ZCD27 ZCP27 ZCD28 ZCMD29L5 ZCMD37L1 ZCT21N12 ZCD31 ZCMD29L1 ZCP37 ZCMD41L2 ZCMD39L1 ZCT26G11 ZCT21G11 ZCMD41L1 ZCMD25L1 ZCD29M12 ZCMD25L5 ZCP28 ZCMD21L08U78 ZCT27P16 ZCD21 ZCT21P16 ZCT26N12 ZCT28G11 ZCMD21L5 ZCMD21L08R12 ZCMD21M12 ZCT28N12 ZCMD81L1 ZCT27G11 ZCMD21L1 ZCT25N12 ZCT26P16 ZCP29M12 ZCP25 ZCD37 ZCT27N12 ZCMD41L5 ZCMD81L5 ZCMD21L2 ZCMD25L2 ZCD29 ZCP39 ZCD39 ZCMD61C12 ZCP21M12 ZCP35 ZCMD69C12 ZCMD39L5 ZCT25G11 ZCP26 ZCMD37L5 ZCP29 ZCD25 ZCD26 ZCD21M12 ZCP31 ZCMD61M12 ZCMD39L2 ZCT28P16 ZCMD29L2 ZCMD29C12 ZCT25P16 ZCP21 ZCD35
Movement of operating head	Linear
Type of operator	Roller plunger spring return metal (with silicone boot)
Type of approach	Lateral approach, 2 directions

## Complementary

Switch actuation	By 30° cam
Positive opening	With

## Environment

Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...70 °C
Environmental characteristic	Standard environment

## Packing Units

Package 1 Weight	0.017 kg
Package 1 Height	0.150 dm
Package 1 width	0.400 dm
Package 1 Length	0.150 dm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Contractual warranty

Warranty	18 months
----------	-----------