



### Main

Range	Prisma
Range of product	Prisma P
Product or component type	Connection
Product name	Prisma P enclosure Masterpact NW circuit breaker
Accessory / separate part category	Current distribution accessory
Standards	IEC 61439-2 IEC 61439-1
Product certifications	ASEFA

### Complementary

Cubicle-device connection	Connection transfer assembly
Poles description	3P
Installation description	Cubicle - width 650 mm
Cubicle depth	600 mm: front 600 + 400 mm: rear
Installed device	Masterpact: drawout NW20...25 - control: toggle vertical installation - bottom connection Masterpact: fixed NW20...25 - control: toggle vertical installation - bottom connection
[I <sub>e</sub> ] rated operational current	2500 A
[I <sub>n</sub> ] rated current	2500 A
Length	580 mm
Quantity per set	Set of 1
Functional unit	650 mm 600 mm Prisma P cubicle Masterpact NW20...25 drawout toggle vertical 3P 1 front connection on adaptor 36 650 mm 1000 mm Prisma P cubicle Masterpact NW20...25 drawout toggle vertical 3P 1 rear connection on adaptor 15 650 mm 600 mm Prisma P cubicle Masterpact NW20...25 drawout toggle vertical 3P 1 front connection on adaptor 20 650 mm 600 mm Prisma P cubicle Masterpact NW20...25 drawout toggle vertical 3P 1 front connection on Canalis 28 650 mm 1000 mm Prisma P cubicle Masterpact NW20...25 drawout toggle vertical 3P 1 rear connection on Canalis 17 650 mm 600 mm Prisma P cubicle Masterpact NW20...25 drawout toggle vertical 3P 1 front connection on busbar 36 650 mm 600 mm Prisma P cubicle Masterpact NW20...25 fixed toggle vertical 3P 1 front connection on adaptor 19 650 mm 1000 mm Prisma P cubicle Masterpact NW20...25 fixed toggle vertical 3P 1 rear connection on adaptor 14 650 mm 600 mm Prisma P cubicle Masterpact NW20...25 fixed toggle vertical 3P 1 front connection on Canalis 28 650 mm 1000 mm Prisma P cubicle Masterpact NW20...25 fixed toggle vertical 3P 1 rear connection on Canalis 16 650 mm 600 mm Prisma P cubicle Masterpact NW20...25 fixed toggle vertical 3P 1 front connection on busbar 36

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	10 kg
Package 1 Height	12 cm
Package 1 width	20 cm
Package 1 Length	61 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>