



### Main

Range	Linergy
Product name	HK
Product or component type	Mounting plate
Poles description	2P
[I <sub>th</sub> ] conventional free air thermal current	25 A
I <sup>2</sup> t on activation	200000 A <sup>2</sup> .s
Number of cables	2 cable(s) 4 mm <sup>2</sup> at 105 °C
Width	54 mm
Height	105 mm
Depth	61 mm

### Complementary

[U <sub>i</sub> ] rated insulation voltage	690 V conforming to IEC 60439-1
9 mm pitches	6
Net weight	0.135 kg






### Environment

Standards	IEC 60439
Product certifications	UL CSA DNV LROS (Lloyds register of shipping)

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	235 g
Package 1 Height	6.3 cm
Package 1 width	7.3 cm
Package 1 Length	12 cm

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

---

Warranty	18 months
----------	-----------

---