



Main

Range	Linergy
Product name	HK
Product or component type	Mounting plate
Poles description	3P + N
[I _{th}] conventional free air thermal current	25 A
I ² t on activation	200000 A ² .s
Number of cables	4 cable(s) 4 mm ² at 105 °C
Width	54 mm
Height	190 mm
Depth	61 mm

Complementary

[U _i] rated insulation voltage	690 V conforming to IEC 60439-1
9 mm pitches	6
Net weight	0.23 kg




Environment

Standards	IEC 60439
Product certifications	UL LROS (Lloyds register of shipping) CSA DNV

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	385 g
Package 1 Height	6.3 cm
Package 1 width	7.5 cm
Package 1 Length	22 cm
Unit Type of Package 2	S03
Number of Units in Package 2	20
Package 2 Weight	8.437 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes

China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------
