



Main

| | |
|---------------------------|--|
| Range | Linergy |
| Range of product | Linergy |
| Product or component type | Busbar |
| Product name | Linergy BW |
| Range compatibility | Prisma G enclosure Prisma P enclosure |
| IP degree of protection | IPxx B |
| Busbar description | Insulated bar |
| Quantity per set | Set of 1 |

Complementary

| | |
|--|--|
| Poles description | 4P |
| Installation direction | Vertical, operating position: rear |
| Installation description | Cubicle - width 650 mm Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm |
| [Ui] rated insulation voltage | 1000 V |
| [Uimp] rated impulse withstand voltage | 8 kV |
| [Ie] rated operational current | 630 A |
| [Icw] rated short-time withstand current | 25 kA (1 s) |
| [Ipk] rated peak withstand current | 52.5 kA |
| I ² t on activation | 625000 kA ² .s |
| Permissible current | 630 A |
| Length | 1000 mm |
| Net weight | 16.64 kg |
| Type of busbar connection | M6 threaded hole |
| Connection pitch | Connection each 25 mm |

Environment

| | |
|------------------------|---|
| Standards | IEC 61439-1 IEC 61439-2 |
| Product certifications | ASEFA |
| Mechanical robustness | Seismic tests - 2.5G conforming to IEC 60068-2-57 |

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 12.6 kg |
| Package 1 Height | 8 cm |
| Package 1 width | 15 cm |
| Package 1 Length | 116.5 cm |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |