



### Main

Range of product	MinerVOLTa
Product or component type	Connection terminal
Accessory / separate part category	Connection accessory

### Complementary

Mounting support	DIN rail
Poles description	1N
[Ue] rated operational voltage	690 V AC
[Icw] rated short-time withstand current	3.5 kAfor 1 s
[Ipk] rated peak withstand current	35.1 kA
Cable cross section	35... 120 mm <sup>2</sup> - AWG 6
Busbar cross section	12 x 5 mm 12 x 10 mm
Creep resistance	200 CTI
IP degree of protection	IP20
Height	160 mm
Width	30 mm
Depth	80 mm
Net weight	215 g

### Environment

Standards	IEC 61439-1:2011 IEC 60999-1:1999 IEC 60999-2:2003
Product certifications	UL 508

### Offer Sustainability

EU RoHS Directive	Not applicable, out of EU RoHS legal scope
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.