04155 ADDITIONAL BLK 2X35² 3P/ LINERGY DP 250A





Main	
Range	Linergy
Range of product	Linergy
Product or component type	Distribution block
Product name	Linergy DP
Range compatibility	Prisma P enclosure Prisma G enclosure Linergy DP distribution block
Accessory / separate part category	Current distribution accessory
IP degree of protection	IPxx B

Complementary

Mounting support	Mounting plate	
Installed device	EasyPact: CVS100250	
	ComPact: NSX100250	
	ComPact: INV100250	
	ComPact: INS100160	
	ComPact: INS250	
Poles description	3P	
[Ue] rated operational voltage	690 V AC	
[Ui] rated insulation voltage	750 V AC	
[Uimp] rated impulse withstand voltage	8 kV	
[le] rated operational current	250 A at 40 °C	
[lcw] rated short-time withstand current	8.5 kAfor 1 s	
[lpk] rated peak withstand current	30 kA	
Connections - terminals	Supply: direct connection120 mm²	
	Distribution: screw terminal, 2 x 35 mm ²	
Net weight	0.235 kg	

Environment

Pollution degree	3	
Overvoltage category	III	
Resistance to incandescent wire	960 °C conforming to IEC 60695-2-11	
Standards	IEC 60947-7-1 IEC 61439-1, inside Prisma IEC 61439-2, inside Prisma	
Product certifications	ASEFA	
Ambient air temperature for operation	-2555 °C	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	235 g	
Package 1 Height	6 cm	
Package 1 width	8 cm	
Package 1 Length	14.5 cm	
Unit Type of Package 2	S02	

Number of Units in Package 2	12
Package 2 Weight	3.281 kg
Package 2 Height	15 cm
Package 2 width	30 cm
Package 2 Length	40 cm
Unit Type of Package 3	P12
Number of Units in Package 3	96
Package 3 Weight	26.24 kg
Package 3 Height	80 cm
Package 3 width	80 cm
Package 3 Length	120 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins