



### Main

Range	Prisma
Range of product	Prisma P
Product or component type	Mounting plate
Accessory / separate part category	Installation accessory
Range compatibility	Prisma P cubicle
Installation description	Cubicle - width 650 mm depth 400 mm
Installed device	<p>EasyPact: fixed CVS100...160 without earth leakage protection - control: direct front rotary handle - vertical installation</p> <p>EasyPact: fixed CVS250 without earth leakage protection - control: direct front rotary handle - vertical installation</p> <p>ComPact: fixed NSX100...160 without earth leakage protection - control: direct front rotary handle - vertical installation</p> <p>ComPact: fixed NSX250 without earth leakage protection - control: direct front rotary handle - vertical installation</p> <p>EasyPact: fixed CVS100...160 with earth leakage protection - control: direct front rotary handle - vertical installation</p> <p>EasyPact: fixed CVS250 with earth leakage protection - control: direct front rotary handle - vertical installation</p> <p>ComPact: fixed NSX100...160 with earth leakage protection - control: direct front rotary handle - vertical installation</p> <p>ComPact: fixed NSX250 with earth leakage protection - control: direct front rotary handle - vertical installation</p> <p>ComPact: fixed NSX100...160 without earth leakage protection - control: motor mechanism - vertical installation</p> <p>ComPact: fixed NSX250 without earth leakage protection - control: motor mechanism - vertical installation</p> <p>ComPact: fixed NSX100...160 with earth leakage protection - control: motor mechanism - vertical installation</p> <p>ComPact: fixed NSX250 with earth leakage protection - control: motor mechanism - vertical installation</p>
Poles description	<p>4 x 3P: fixed CVS100...160 vertical installation</p> <p>3 x 4P: fixed CVS100...160 vertical installation</p> <p>4 x 3P: fixed CVS250 vertical installation</p> <p>3 x 4P: fixed CVS250 vertical installation</p> <p>4 x 3P: fixed NSX100...160 vertical installation</p> <p>3 x 4P: fixed NSX100...160 vertical installation</p> <p>4 x 3P: fixed NSX250 vertical installation</p> <p>3 x 4P: fixed NSX250 vertical installation</p>

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Number of vertical modules [50 mm]	<p>9 module(s): CVS100...160 without earth leakage protection , direct in 650 mm Widecubicle</p> <p>9 module(s): CVS250 without earth leakage protection , direct in 650 mm Widecubicle</p> <p>6 module(s): NSX100...160 without earth leakage protection , Linergy FC in 650 mm Widecubicle</p> <p>8 module(s): NSX100...160 without earth leakage protection , direct in 650 mm Widecubicle</p> <p>7 module(s): NSX250 without earth leakage protection , Linergy FC in 650 mm Widecubicle</p> <p>9 module(s): NSX250 without earth leakage protection , direct in 650 mm Widecubicle</p> <p>11 module(s): CVS100...160 with earth leakage protection , direct in 650 mm Widecubicle</p> <p>11 module(s): CVS250 with earth leakage protection , direct in 650 mm Widecubicle</p> <p>8 module(s): NSX100...160 with earth leakage protection , Linergy FC in 650 mm Widecubicle</p> <p>10 module(s): NSX100...160 with earth leakage protection , direct in 650 mm Widecubicle</p> <p>9 module(s): NSX250 with earth leakage protection , Linergy FC in 650 mm Widecubicle</p> <p>11 module(s): NSX250 with earth leakage protection , direct in 650 mm Widecubicle</p>
Standards	IEC 61439-2
Product certifications	ASEFA

### Complementary

Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Surface finish	Matt Smooth
Colour	White
Width	606 mm
Height	147 mm
Depth	372 mm

Net weight	2.28 kg
Functional unit	<p>650 mm 400 mm Prisma P cubicle EasyPact CVS100...160 without fixed direct front rotary handle vertical 3P 4 direct 9 162.5 mm</p> <p>650 mm 400 mm Prisma P cubicle EasyPact CVS100...160 without fixed direct front rotary handle vertical 4P 3 direct 9 162.5 mm</p> <p>650 mm 400 mm Prisma P cubicle EasyPact CVS250 without fixed direct front rotary handle vertical 3P 4 direct 9 162.5 mm</p> <p>650 mm 400 mm Prisma P cubicle EasyPact CVS250 without fixed direct front rotary handle vertical 4P 3 direct 9 162.5 mm</p> <p>650 mm 400 mm Prisma P cubicle ComPact NSX100...160 without fixed direct front rotary handle vertical 3P 4 Linergy FC 6 62.5 mm</p> <p>650 mm 400 mm Prisma P cubicle ComPact NSX100...160 without fixed motor mechanism vertical 3P 4 Linergy FC 6 62.5 mm</p> <p>650 mm 400 mm Prisma P cubicle ComPact NSX100...160 without fixed direct front rotary handle vertical 4P 3 Linergy FC 6 62.5 mm</p> <p>650 mm 400 mm Prisma P cubicle ComPact NSX100...160 without fixed motor mechanism vertical 4P 3 Linergy FC 6 62.5 mm</p> <p>650 mm 400 mm Prisma P cubicle ComPact NSX100...160 without fixed direct front rotary handle vertical 3P 4 direct 8 162.5 mm</p> <p>650 mm 400 mm Prisma P cubicle ComPact NSX100...160 without fixed direct front rotary handle vertical 4P 3 direct 8 162.5 mm</p> <p>650 mm 400 mm Prisma P cubicle ComPact NSX100...160 without fixed motor mechanism vertical 3P 4 direct 8 162.5 mm</p> <p>650 mm 400 mm Prisma P cubicle ComPact NSX100...160 without fixed motor mechanism vertical 4P 3 direct 8 162.5 mm</p> <p>650 mm 400 mm Prisma P cubicle ComPact NSX250 without fixed direct front rotary handle vertical 3P 4 Linergy FC 7 62.5 mm</p> <p>650 mm 400 mm Prisma P cubicle ComPact NSX250 without fixed motor mechanism vertical 3P 4 Linergy FC 7 62.5 mm</p> <p>650 mm 400 mm Prisma P cubicle ComPact NSX250 without fixed direct front rotary handle vertical 4P 3 Linergy FC 7 62.5 mm</p> <p>650 mm 400 mm Prisma P cubicle ComPact NSX250 without fixed motor mechanism vertical 4P 3 Linergy FC 7 62.5 mm</p> <p>650 mm 400 mm Prisma P cubicle ComPact NSX250 without fixed direct front rotary handle vertical 3P 4 direct 9 162.5 mm</p> <p>650 mm 400 mm Prisma P cubicle ComPact NSX250 without fixed direct front rotary handle vertical 4P 3 direct 9 162.5 mm</p> <p>650 mm 400 mm Prisma P cubicle ComPact NSX250 without fixed motor mechanism vertical 3P 4 direct 9 162.5 mm</p> <p>650 mm 400 mm Prisma P cubicle ComPact NSX250 without fixed motor mechanism vertical 4P 3 direct 9 162.5 mm</p> <p>650 mm 400 mm Prisma P cubicle ComPact NSX100...160 with fixed motor mechanism vertical 4P 3 Linergy FC 8 62.5 mm</p> <p>650 mm 400 mm Prisma P cubicle ComPact NSX100...160 with fixed direct front rotary handle vertical 3P 4 direct 10 162.5 mm</p> <p>650 mm 400 mm Prisma P cubicle ComPact NSX100...160 with fixed direct front rotary handle vertical 4P 3 direct 10 162.5 mm</p> <p>650 mm 400 mm Prisma P cubicle ComPact NSX100...160 with fixed motor mechanism vertical 3P 4 direct 10 162.5 mm</p> <p>650 mm 400 mm Prisma P cubicle ComPact NSX100...160 with fixed motor mechanism vertical 4P 3 direct 10 162.5 mm</p> <p>650 mm 400 mm Prisma P cubicle ComPact NSX250 with fixed direct front rotary handle vertical 3P 4 Linergy FC 9 62.5 mm</p> <p>650 mm 400 mm Prisma P cubicle ComPact NSX250 with fixed motor mechanism vertical 3P 4 Linergy FC 9 62.5 mm</p> <p>650 mm 400 mm Prisma P cubicle ComPact NSX250 with fixed direct front rotary handle vertical 4P 3 Linergy FC 9 62.5 mm</p> <p>650 mm 400 mm Prisma P cubicle ComPact NSX250 with fixed motor mechanism vertical 4P 3 Linergy FC 9 62.5 mm</p> <p>650 mm 400 mm Prisma P cubicle ComPact NSX250 with fixed direct front rotary handle vertical 3P 4 direct 11 162.5 mm</p> <p>650 mm 400 mm Prisma P cubicle ComPact NSX250 with fixed direct front rotary handle vertical 4P 3 direct 11 162.5 mm</p> <p>650 mm 400 mm Prisma P cubicle ComPact NSX250 with fixed motor mechanism vertical 3P 4 direct 11 162.5 mm</p> <p>650 mm 400 mm Prisma P cubicle ComPact NSX250 with fixed motor mechanism vertical 4P 3 direct 11 162.5 mm</p>

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	2.28 kg
Package 1 Height	3 cm
Package 1 width	15.5 cm
Package 1 Length	58 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
Halogen content performance	Halogen free plastic parts product