

Main

Range	Prisma
Range of product	Prisma G
Product or component type	Mounting plate
Accessory / separate part category	Installation accessory
Range compatibility	Prisma G enclosure
Installation description	Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm
Installed device	FuPact: fixed ISFT100N - control: fuse carriers handle - vertical installation
Poles description	8 x 3P: fixed ISFT100N vertical installation
Number of vertical modules [50 mm]	8 module(s): ISFT100N, direct in 600 mm Widefloor-standing enclosure 8 module(s): ISFT100N, direct in 600 mm Widewall-mounted enclosure
Standards	IEC 61439-2
Product certifications	ASEFA




Complementary

Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Surface finish	Smooth Matt
Colour	White (RAL 9001)
Width	600 mm
Height	100 mm
Depth	94 mm
Net weight	1.15 kg
Functional unit	600 mm Prisma G floor-standing enclosure FuPact ISFT100N fixed fuse carriers handle vertical 3P 8 direct 8 175 mm 600 mm Prisma G wall-mounted enclosure FuPact ISFT100N fixed fuse carriers handle vertical 3P 8 direct 8 175 mm

Packing Units

Package 1 Weight	1.150 kg
Package 1 Height	1.000 dm
Package 1 width	1.020 dm
Package 1 Length	4.700 dm

Offer Sustainability

Sustainable offer status	Green Premium product
RECh Regulation	 RECh Declaration
RECh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes

China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
Halogen content performance	Halogen free plastic parts product
