



Main

Range	Prisma
Range of product	Prisma P
Product or component type	Mounting plate
Accessory / separate part category	Installation accessory
Range compatibility	Prisma P cubicle
Installation description	Cubicle - width 650 mm depth 400 mm
Installed device	FuPact: fixed ISFT100 - control: fuse carriers handle - vertical installation
Poles description	5 x 3P: fixed ISFT100 vertical installation
Number of vertical modules [50 mm]	6 module(s): ISFT100, direct in 650 mm Widecubicle
Standards	IEC 61439-2
Product certifications	ASEFA

Complementary

Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Surface finish	Matt Smooth
Colour	White (RAL 9001)
Width	620 mm
Height	156 mm
Depth	363 mm
Net weight	1.9 kg
Functional unit	650 mm 400 mm Prisma P cubicle FuPact ISFT100 fixed fuse carriers handle vertical 3P 5 direct 6 77.5 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.9 kg
Package 1 Height	4 cm
Package 1 width	15 cm
Package 1 Length	58 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	12
Package 2 Weight	23.68 kg
Package 2 Height	20 cm
Package 2 width	40 cm
Package 2 Length	60 cm
Unit Type of Package 3	P12
Number of Units in Package 3	48
Package 3 Weight	94.72 kg
Package 3 Height	80 cm
Package 3 width	80 cm
Package 3 Length	120 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
Halogen content performance	Halogen free plastic parts product