



### Main

Range	Spacial
Product or component type	Drive flush mounting kit
Accessory category	Mounting and fixing accessory
Product specific application	Process and utilities
Range compatibility	Altivar variable speed drive ATV630 Altivar variable speed drive ATV930 Spacial SF and SM enclosures: H:>=500 mm x W:>=300 mm Spacial S3D enclosure: H:>=500 mm x W:>=300 mm
Compatibility for Altivar Process 630-930, size:	2
Motor power kW	5.5 KW 220/240 V 7.5 KW 380/480 V 11 kW
Mounting location	Mode 1: back of enclosure on mounting plate Mode 2: inside enclosure
Kit composition	1 x mounting plate with flanges and integrated gasket, steel with anti-corrosive coating. Fixing by screws and nuts 1 x fixing accessories 1 x drilling template 1 x instruction sheet 1 x edge protector profile, plastic.

### Complementary

Permanent permissible load	7.7 kg
Colour	Grey (RAL 7035)
Height	420 Mm external: 375 mm cut-out:
Width	265 Mm external: 215 mm cut-out:
Depth	22 mm wall-enclosure separation:
Net weight	1.922 kg
Services	Configuration of enclosure pre-drilled back at requested dimensions Factory installation drive flush mounting kit on enclosure

### Environment

IP degree of protection	IP55 conforming to IEC 60529
-------------------------	------------------------------

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.909 kg
Package 1 Height	5.2 cm
Package 1 width	28.6 cm
Package 1 Length	43 cm
Unit Type of Package 2	S04
Number of Units in Package 2	5
Package 2 Weight	10.797 kg

Package 2 Height	30 cm
Package 2 width	40 cm
Package 2 Length	60 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>