



### Main

Range	Spacial
Product or component type	Drive flush mounting kit
Accessory category	Mounting and fixing accessory
Product specific application	Process and utilities
Range compatibility	Altivar variable speed drive ATV630 Altivar variable speed drive ATV930 Spacial SF and SM enclosures Altivar variable speed drive ATV340
Compatibility for Altivar Process 630-930, size:	4
Motor power kW	15 KW 220/240 V 18.5 KW 220/240 V 22 KW 220/240 V 30 KW 380/480 V 37 KW 380/480 V 45 kW 380/480 V
Mounting location	Mode 1: back of enclosure on mounting plate Mode 2: inside enclosure
Kit composition	1 x mounting plate with flanges and integrated gasket, steel with anti-corrosive coating. Fixing by screws and nuts 1 x fixing accessories 1 x drilling template 1 x instruction sheet 1 x edge protector profile, plastic. 1 x fan support 1 x cover for fan protection

### Complementary

Permanent permissible load	28.7 kg
Colour	Grey (RAL 7035)
Height	800 Mm external: 735 mm cut-out:
Width	385 Mm external: 325 mm cut-out:
Depth	151.5 mm wall-enclosure separation:
Net weight	8.102 kg
Services	Configuration of enclosure pre-drilled back at requested dimensions Factory installation drive flush mounting kit on enclosure

### Environment

IP degree of protection	IP55 conforming to IEC 60529
-------------------------	------------------------------

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	5 kg
Package 1 Height	12 cm
Package 1 width	20 cm
Package 1 Length	84 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>