



Main

| | |
|-----------------------------|--------------------------------|
| Product or component type | Auxiliary contact |
| Device short name | PF |
| Range compatibility | MasterPact NT Masterpact NW |
| Signal contacts composition | 1 NO/NC |

Complementary

| | |
|---------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Auxiliary contacts type | Standard |
| Mounting mode | Fixed |
| [I _e] rated operational current | AC-12: 5 A at 480 V AC 50/60 Hz AC-12: 3 A at 690 V AC 50/60 Hz AC-12: 5 A at 240/380 V AC 50/60 Hz DC-12: 0.15 A at 250 V DC DC-12: 3 A at 24/48 V DC DC-12: 0.3 A at 125 V DC |
| Minimum load | 100 mA at 24 V |

Offer Sustainability

| | |
|----------------------------|------------------------------------------------------------------------------------------------|
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|