



### Main

|                             |                   |
|-----------------------------|-------------------|
| Product or component type   | Auxiliary contact |
| Device short name           | SDE               |
| Range compatibility         | Masterpact NW     |
| Signal contacts composition | 1 NO/NC           |

### Complementary

|   |  |
|---|--|
| Auxiliary contacts type                     | Low level  |
| Mounting mode                               | Drawout  |
| [I <sub>e</sub> ] rated operational current | DC-12: 0.15 A at 250 V DC<br>DC-12: 3 A at 24/48 V DC<br>AC-12: 3 A at 24/48 V AC 50/60 Hz<br>AC-12: 3 A at 240 V AC 50/60 Hz<br>DC-12: 0.3 A at 125 V DC<br>AC-12: 3 A at 380 V AC 50/60 Hz |
| Minimum load                                | 2 mA at 15 V   |

### Offer Sustainability

|                            |   |
|----------------------------|---|
| REACH Regulation           | <a href="#">REACH Declaration</a>             |
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>                           |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>        |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|