



### Main

Range of product	Acti 9
Product or component type	Fault contact
Device short name	SDV NF
Signal contacts composition	1 NC
[In] rated current	0.1...1 A: 250 V AC - 50/60 Hz
9 mm pitches	1

### Complementary

Range compatibility	Vigi NG125
[Ui] rated insulation voltage	690 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
Mounting mode	Plug-on
Mounting location	Upstream
Height	36 mm
Width	8.8 mm
Depth	34.64 mm
Electrical durability	10000 cycles
Connections - terminals	Plate terminal1 cable(s) 0.5...2.5 mm <sup>2</sup> - rigid Plate terminal1 cable(s) 0.5...1.5 mm <sup>2</sup> - flexible Plate terminal1 cable(s) 0.5...1.5 mm <sup>2</sup> - flexible with ferrule Plate terminal2 cable(s) 2.5 mm <sup>2</sup> - rigid Plate terminal2 cable(s) 2.5 mm <sup>2</sup> - flexible Plate terminal2 cable(s) 1.5 mm <sup>2</sup> - flexible with ferrule
Wire stripping length	10 mm
Tightening torque	1 N.m

### Environment

Pollution degree	3
Tropicalisation	2
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...85 °C

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	35 g
Package 1 Height	2.5 cm
Package 1 width	8 cm
Package 1 Length	10.6 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	9
Package 2 Weight	380 g
Package 2 Height	11.5 cm

Package 2 width	8.5 cm
Package 2 Length	23.7 cm
Unit Type of Package 3	S03
Number of Units in Package 3	81
Package 3 Weight	3.942 kg
Package 3 Height	30 cm
Package 3 width	30 cm
Package 3 Length	40 cm

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Circularity Profile	<a href="#">End Of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

### Contractual warranty

Warranty	18 months
----------	-----------