



Main

Range	Vigirex
Product or component type	Earth leakage current sensor
Device application	Equipment monitoring and control
Current sensor type	Rectangular sensor
[Ie] rated operational current	3200 A

Complementary

Transformer ratio	1/1000
[Icw] rated short-time withstand current	100 kAfor 0.5 s
Residual short-circuit withstand current	85 kA / 0.5 s
Overvoltage category	IV
[Uimp] rated impulse withstand voltage	12 kV
Mounting mode	Fixed (cables) Fixed (busbar)
Connections - terminals	Screw connection 0.2...2.5 mm ²
Net weight	21.16 kg
Height	Outside: 281 mm Inside: 160 mm
Width	Outside: 572 mm Inside: 470 mm
Height	281 mm
Depth	Outside: 72 mm Inside: 72 mm
Width	572 mm
Depth	72 mm

Environment

IP degree of protection	Connectors: IP20 IP30
Environmental characteristic	Exposure to damp heat not in service (25...55 °C, RH 95 %) : 28 cycles conforming to IEC 60068-2-30 Salt mist: Kb/2 conforming to IEC 60068-2-52 Exposure to damp heat in service: category C2: 48 hours conforming to IEC 60068-2-56
Ambient air temperature for operation	-35...80 °C
Ambient air temperature for storage	-55...100 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	18.05 kg
Package 1 Height	18 cm
Package 1 width	35 cm
Package 1 Length	66 cm

Unit Type of Package 2	P12
Number of Units in Package 2	9
Package 2 Weight	199.668 kg
Package 2 Height	80 cm
Package 2 width	80 cm
Package 2 Length	120 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------