Product data sheet Characteristics

LV432517

plug in base, ComPact NSX 400/630, front/rear connected, 4 poles





Plug-in base
Mounting accessory
ComPact NSX400 ComPact NSX630 Compact NSX400 DC Compact NSX630 DC
4P

Complementary

Mounting mode	Plug-in
[ln] rated current	630 A
Earth-leakage protection	Without

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	3.64 g
Package 1 Height	11.5 cm
Package 1 width	20 cm
Package 1 Length	35 cm
Unit Type of Package 2	S04
Number of Units in Package 2	5
Package 2 Weight	19.006 kg
Package 2 Height	30 cm
Package 2 width	40 cm
Package 2 Length	60 cm
Unit Type of Package 3	P12
Number of Units in Package 3	20
Package 3 Weight	88.364 kg
Package 3 Height	80 cm
Package 3 width	80 cm
Package 3 Length	120 cm

Offer Sustainability

RoHS exemption information	Sustainable offer status	Green Premium product	
Mercury free Yes RoHS exemption information Compliant Feb RoHS Declaration Yes	REACh Regulation	REACh Declaration	
RoHS exemption information	EU RoHS Directive	Compliant EEU RoHS Declaration	
The state of the s	Mercury free	Yes	
Environmental Disclosure	RoHS exemption information	₫Yes	
Product Environmental Profile	Environmental Disclosure	Product Environmental Profile	

WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes
Contractual warranty	
Warranty	18 months