



Main

Range of product	ComPact NSX100...250 ComPact NSX400...630
Range	ComPact
Device short name	SDTAM
Product or component type	Thermal fault module
Device application	Signalling
Range compatibility	ComPact NSX circuit breaker
Accessory / separate part category	Trip unit accessory
Trip unit name	Micrologic 2.3 M Micrologic 2.2 M Micrologic 6.3 E-M Micrologic 6.2 E-M

Complementary

Maximum output current	0.08 A
[Us] rated supply voltage	24...415 V AC 50/60 Hz 24...415 V DC

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	58 g
Package 1 Height	4 cm
Package 1 width	5 cm
Package 1 Length	10.5 cm
Unit Type of Package 2	S02
Number of Units in Package 2	46
Package 2 Weight	3.123 kg
Package 2 Height	15 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Circularity Profile

 [End Of Life Information](#)

WEEE

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty

18 months
