Product data sheet Characteristics

33734

front connections, 630 A to 1600 A, drawout circuit breaker, bottom mounting, 4 poles



Main		
Product or component type	Front connection	
Accessory / separate part category	Connection accessory	
Range compatibility	MasterPact NT circuit breaker MasterPact NT switch disconnector ComPact NS630b1600 circuit breaker ComPact NS630b1600 switch disconnector	
Poles description	4P	
[In] rated current	630 A H1 drawout 630 A H2 drawout 630 A H3 drawout 630 A L1 drawout 800 A H1 drawout 800 A H2 drawout 800 A H3 drawout 800 A H3 drawout 1000 A H1 drawout 1000 A H1 drawout 1000 A H2 drawout 1000 A H3 drawout 1000 A H1 drawout 1250 A H1 drawout 1250 A H2 drawout 1250 A H2 drawout 1250 A H3 drawout 1600 A H1 drawout 1600 A H2 drawout 1600 A H2 drawout 1600 A H3 drawout 1600 A H4 drawout 1600 A HA drawout 1600 A HA drawout 1600 A HA drawout 1600 A HA drawout 1000 A HA drawout	

Complementary

Location of connection	Front	
Localisation on device	Downside	
Connection pitch	70 mm	

Offer Sustainability

REACh Regulation	[™] REACh Declaration	
EU RoHS Directive	Compliant EPEU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	€Yes	
China RoHS Regulation	China RoHS Declaration	
PVC free	Yes	

Contractual warranty

Ochitacidal Warranty		
Warranty	18 months	